

Wire saw CSA-100 H



storage rolls	8
wire in storage min/max	4,0/10,5 m
max. wire storage capacity	6,5 + 1,5* m
weight without motor	54 kg
operational weight without wire	60,8 kg
oil flow capacity feed	1 - 15 l/min
max. operating pressure feed	100 bar
dimensions L/W/H	1050/300/460 mm

* by displacing the machine on the mounting tube

order-No.	description
55 83	automatic wire saw with 2 mini swivel rolls and ground mounting foot, without drive motor
55 88	wire guard set with water collecting function
50 70	hydraulic drive motor 19 cm ³
54 09	hydraulic power pack, 15 kW/400 V, 30/44/6 l/min, 250 bar
54 12	hydraulic control panel for HAG-12.2 for feed control
50 53	set of hoses 3-parts, 10 m long, for drive of drive wheel (wire saw)
50 50	set of hoses 2-parts, 10 m long, for feed at wire sawing with hydraulic control panel

order-No.	description
50 71	hydraulic drive motor 23 cm ³ , alternatively to HM-19
54 05	hydraulic power pack, 15 kW/400 V, 30/44 l/min, 250 bar, combined with HSP-12 alternatively to HAG-12.2 with hydraulic control panel
48 85	hydraulic control panel
48 83	set of hoses 2-parts, 10 m long, for feed at drilling and wire sawing
55 85	foot for mounting to wall or ground with mounting tube
55 86	precision swivel foot 360° with mounting tube
49 07	set of anchoring dowels M12 with impact nut